

# BIO SMART™

*Therapeutic Infrared Heat*



## BIO-1000F In-Wall Edition

All metal **Chassis**, 22 & 24 gauge, with synthetic, paintable shell

**Chassis size** is 16" x 12 5/8" x 4" (HxWxD) / 13 lbs

120 volt or 220 volt AC, 1000 watt **Power Requirement**

4800 BTU equivalent **Heat Output**

Ceramic insulated plate **Infrared Emitters**

40,000 hour **Emitter Life Expectancy**

**Safety Cut-Off** prevents damage to the unit

**Chassis Safety Insulation** exceeds all government and independent laboratory standards for safety

cTUVus Int'l **Certification** (UL/CSA equivalent)

**Zoned Heat Capability:** Pre-wired - simple two-wire contact to any zone control panel

Proprietary **Heating Chamber** with copper-ion generation panels

Heats with **safe, therapeutic Far-Infrared** waves

**System Noise Level** is only 18 dB

**Thermostat Type:** Any standard digital, programmable, or mechanical (no in line high voltage)

**Installation:** Any wall with a minimum 3 1/2 inches of depth

**Rough opening** is 15 1/2" x 12 3/4" (HxW)

Save energy with **Zoned-Heating Capability**

25 years+ **Life Expectancy**

5-Year **Limited Warranty**