

BIO SMART™

Therapeutic Infrared Heat



BIO-1400 OWA On-Wall Edition with Air Purification

All metal **Chassis**, 22 & 24 gauge, with synthetic, paintable shell

22" x 13" x 5" (HxWxD) / 19 lbs

120 volt AC, 1400/700 watt **Power Requirement** (220 volt configuration available upon request).

1400 watt (Hi) / 700 watt (Lo) **Power Settings**

6,300 BTU equivalent **Heat Output** on Hi

Heats up to **800 sq ft** on Hi

3 - Probe electronic **digital Thermostat**; Range 37 - 86 °F

Delay Start up to 24 hours

System Noise Level only 18 dB on low, 28 db on high

40,000 hour **Emitter Life Expectancy**

3 - Stage Air Purifier (UV, TiO₂, and Ionizer), can be run independent of the heater

Heats with **safe, therapeutic Far-Infrared** waves

Proprietary **Heating Chamber** with copper-ion generation panels

Dual Speed, high-output, ball bearing laminar-flow **Fan**

Easy to use **Remote Control** in credit-card style

Automatically Restarts after a power outage

Safety Cut-Off prevents damage to the unit

Chassis Safety Insulation exceeds all government and independent laboratory standards for safety

Save energy with **Zoned-Heating Capability**

7 ft **power cord** plugs into grounded wall outlet

Includes wall-mounting supplies for **Easy Installation**

cTUVus Int'l **Certification** (UL/CSA equivalent)

5-Year limited **Warranty**